

SHIBAURA

PRICE LIST 2012



SHIBAURA

- * Lawn- & garden tractor
- * Frontmowers
- * Fairway mowers
- * Handgreensmower
- * Rough terrain-/ slopemower
- * Subcompact tractor
- * Compact tractors
- * Accessories



SHIBAURA
EUROPE

Shibauro Europe BV
Begonialaan 7
NL - 6851 TE Huissen
The Netherlands
T. 0031 26326 9999
F. 0031 26326 9990
E. info@shibauro.com
www.shibauro.com

Shibaura

Ishikawajima Shibaura Machinery Co. Ltd. was established in 1950 by two companies, Toshiba (Tokyo-Shibaura-Engineering) and IHI (Ishikawajima Harima Industries). Originally Shibaura started as manufacturer of engines. In 1961 a factory was completed for the production of tractors up to 40 hp, both two-wheel drive and four-wheel drive version. Shibaura is producing in three factories. A complete new engine factory in Asashi. An other factory in Matsumoto is producing tractors, frontmowers en golfcourse machinery, with an area of approx. 14 ha. Total annual production capacity is 50,000 units. In Okayama a factory, with an area of approx. 3 ha, for the production of ozone-equipment. Beside these three factories in Japan, Shibaura has together with Perkins factories in UK, USA and for some time in China.

Group company IHI

Shibaura is an affiliate company of the IHI Corporation. IHI is a leading heavy industrial group of companies in Japan, operating in the field of aerospace, jet engines, power plants, bridges, industrial machineries and shipbuilding. Total turnover is USD 10 billion with 7,200 employees. At Shibaura 900 employees are working.

Shibaura products

Shibaura products: ride-on mower, compacttractors and professional mowers have build up a reputation of fine quality.

In fast speed the programme is extended and is adapted to the wishes of the users in the several countries. By concentration also on the European market now a very modern range of tractors can be offered 18 to 60 hp, both mechanically and hydrostatically operated.

The extremely modern frontmowers 21, 30 and 36 hp are provided with engines which come up to all standards, with relatively large displacement, low noise level and high pulling power. Provided with automatic four wheel drive.

Important in the programme is the SX24 subcompacttractor with hydrostatic transmission and 24 hp. Multifunctional tractor for all kind of work; grass mowing and catching, pulling, tilling and ploughing. But also for the winter period, for example snow moving and snowblowing. Particularly high tech product for a very attractive price.

New products are the SR370 three-gang fairway mower, slopemower SG280, ST450LST 50 HP hydrostatic tractor and the ST460EHSS 60 HP tractor.

Shibaura is an important manufacturer of ozone equipment for bacterium suppression in hospitals and at calamities, but also for sport fields.

Shibaura Europe B.V.

For better service to our customers on April 1 st. 1991 Shibaura Europe was founded. This way a full 100% attention can be paid to Shibaura products and both customers and dealers are assured of excellent service. We think this catalogue gives you a complete overview of products that Shibaura has to offer. We would be pleased to send you further information. You are also very welcome to visit our website (www.shibaura.com) or to visit our office on the industrial area Huissen-Bemmel at the end of highway A15.

Shibaura Europe B.V.
ir. P.J.M. Franken
Managing Director

Shibaura Europe B.V.
ir. W.W.J. Broekstra
Managing Director

CONTENTS:

	PAGE:		PAGE:
Shibaura GT161	2	Shibaura ST333M/ ST333HST	23
Shibaura CM214	4	Shibaura ST445SSS	26
Shibaura CM314/ CM374	6	Shibaura ST450HST	28
Shibaura SR370	9	Shibaura ST460EHSS	29
Shibaura SR525	10	Prices tires and wheels	30
Shibaura GM222	12	Complete engines	30
Shibaura SG280	13	Rotary mowers	31
Shibaura SX24	14	Flailmowers	31
Shibaura ST318M/ ST318HST	17	Fertilizer-/ saltspreader	31
Shibaura ST321M/ ST321HST	18	Snowblower	32
Shibaura ST324M/ ST324HST	19	Artificial turf maintenance	33
Shibaura ST330M/ ST330HST	22		

**All prices are in EURO excl. VAT. Prices and technical details are subject to change without previous notice.
All deliveries according to AHL 92.**

SHIBAURA EUROPE BV

Begonialaan 7	Phone	0031 26 326 9999
NL - 6851 TE Huissen	Fax.	0031 26 326 9990
the Netherlands	GSM	0031 654314001 (Paul Franken)
Internet: www.shibaura.com		0031 629544770 (Wendy Broekstra)
E-mail: info@shibaura.com		0031 621883620 (Erik Pelle)
		0031 621534773 (Patrick Janssen)

Chamber of Commerce Arnhem 10036098
VAT. nr. NL009486938B01

Rabo Bank nr. 12.40.42.775
Swiftcode: RABONL2U
IBAN: NL92 RABO 0124 0427 75

	<i>Phone:</i>		<i>E-mail:</i>
Sales Benelux	Erik Pelle	0031 621883620	pelle@shibaura.com
Sales/ Spareparts	Bert Meijer	0031 26 3269991	meijer@shibaura.com
Technical Service	Patrick Janssen	0031 26 3269993	janssen@shibaura.com
Administration	Angélique Rutten	0031 26 3269996	rutten@shibaura.com
Managing Director	Wendy Broekstra	0031 26 3269997	broekstra@shibaura.com
Managing Director	Paul Franken	0031 26 3269995	franken@shibaura.com

Shibaura Deutschland GmbH Carl-Hans-Straße 4 D-51674 Wiehl

Phone/ Fax		0049 2296 999010	0049 2296 9990111
Sales Germany North	Werner Schmelz	0049 171 1745857	schmelz@shibaura.de
Sales Germany South	Udo Sager	0049 151 40137672	sager@shibaura.de
Sales/ Spareparts	Georg Happ	0049 2296 9990112	happ@shibaura.de
Technical Service	Marcel Kreps	0049 2296 9990115	kreps@shibaura.de
Technical Service	Jörg Schnabel	0049 2296 9990115	info@shibaura.de
Administration	Heike Latzke	0049 2296 9990114	info@shibaura.de

SHIBAURA EUROPE BV

SHIBAURA LAWN-AND GARDEN TRACTOR GT161

ENGINE	3 cylinder, low noise, watercooled Shibaura dieselmotor 14.4 kW / 20 hp (SAE) 12.5 kW / 17 hp (DIN) 676 cc
FUEL TANK CAPACITY	16 litres
STARTING SYSTEM	Elektric
TRANSMISSION	Hydrost./2 groups: forwards: 0-6.6 km/h und 0-12.8 km/h backwards: 0-3.3 km/h und 0-6.4 km/h
TURNING RADIUS	810 mm
POWERSTEERING	Standard
MIDMOUNT MOWER SIDE DISCHARGE	cutting width 1.22 m cutting height 25-108 mm/ 13 stages
LxWxH	1910x990x1210 mm, excl. mower
WEIGHT	382 kg

- Hydraulic lift of the mower!
- Adjustable steer
- Mower transmission with PTO
- Safety switches in seat, brake and PTO
- Oil pressure lamp, fuel indicator and towing plate
- Speed control

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
GT161	GT161 Lawn- and garden tractor, without mower	8,800,-
SGM48	Subsequent delivery mower 1.22 m	2,700,-
PA-123SH	Extra price mulching system (net)	650,-
GTMAAIMID	Extra price rear discharge (net)	690,-



ACCESSORIES SHIBAURA GT161

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
	CABIN	
LX-11	Walter Mauser Cabin incl. comfort kit and heating Mounting (net)	3,730,- 320,-
	KERSTEN FRONTLIFT	
FKDR-HY	Hydraulic frontlift needed for mounting sweeper or blade (mower can stay on the tractor)	1,860,-
	KERSTEN SWEEPER (only with FKDR-HY)	
FKM1255HA	Sweeper 1.25 x ø 0,37 m	2,030,-
1255200	Rubber mud flap 1.25 m	200,-
1255300	Dust collector 1.25 m	640,-
1050400	Side brush ø 0.40 m	515,-
1000600	Dismounting frame with wheels	140,-
1000510	Tank- and spraying equipment with 2 nozzles	360,-
	KERSTEN FRONTBLADE (only with FKDR-HY)	
SF1255KD	Snowblade with spring flaps incl. plastic scraping rib 1.25x0.45m	975,-



SHIBAURA FRONTMOWER CM214

AUTOMATIC FOURWHEELDRIVE

When the front wheels are slipping, the 4% fourwheeldrive is automatically engaged.

ENGINE

3 cylinder, low noise, watercooled Shibaura diesel engine
17.6 kW/ 24 hp (SAE) 16.0 kW/ 21.7 hp (DIN) 1005 cc

TRANSMISSION

Hydrostatic: forwards: 0-14 km/h
backwards: 0-8 km/h

TURNING RADIUS

150 cm

PTO

2200 rpm.

FUEL TANK CAPACITY

28 litres

LxWxH

2130x1000x1875 mm

GROUND CLEARANCE

125 mm

TREAD

front: 800 mm rear: 830 mm

WEIGHT with ROB

530 kg

- Powersteering
- Auto/ full time 4WD can be switch on from the seat
- Safety switch in seat, PTO and brakes
- Weight transfer from mower to tractor

Code:
CM214

Description:
CM214 without mower
with turf tires

F: 20x10.00-8;

R: 16x6.50-8

Euro:
15,300,-



ACCESSORIES SHIBAURA CM214

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
SCM48S	SHIBAURA FRONTMOWER 1.22 m side discharge 7 stages cutting height adjustments from 25-115 mm, mower can be lifted up for easy cleaning and maintenance, 120 kg	3,100,-
PA-123SH	Mulchset (net)	650,-
8380040 1200450	WIEDENMANN mower 1.30 m rear discharge Mulchset	4,990,- 570,-
TMC-F 120 V01D50	MORGNIEUX mower 1.20 m rear discharge Mulchset	3,400,- 540,-
MUC100-31-1	MÜTHING Flailmower 1.00 m	3,300,-
KS214	WALTER MAUSER CABIN (incl. heating) Mounting (net)	4,500,- 250,-
PM500	GRASSCOLLECTOR 500 litres, high dump 1.80 m Mounting (net)	6,055,- 630,-
FKM1250GE 1250350 1250450	KERSTEN SWEEPER 1.25 x ø 0.37 m Dust collector 1.25 m Sidebrush ø 0.40 m	3,515,- 1,310,- 660,-
SF1355AO 0111 SH016019	KERSTEN FRONTBLADE incl. hydr. side adj. Attachment system necessary for sweeper and frontblade Hydr. set with 2 quick coupling (necessary for hydr. side adj.)	2,080,- 525,- 820,-
100EL	HYDROMANN SPREADER with agitator 100 litres, 12 volt	3,140,-
KS40WD	APV SALTSREADER 40 litres, electric driven Mounting (net)	1,480,- 220,-



SHIBAURA FRONTMOWER CM314/ CM374

AUTOMATIC FOURWHEELDRIVE

When the front wheels are slipping, the 4% fourwheeldrive is automatically engaged.

ENGINE

3 cylinder, low noise, watercooled Shibaura diesel engine
CM314 25.5 kW/33.8hp (SAE) 22.4 kW/30.0hp (DIN) 1496 cc
CM374 29.4 kW/40hp (SAE) 26.0 kW/36.3hp (DIN) 1662 cc

TRANSMISSION

Hydrost./ 2 groups: forwards: 0-10 km/h and 0-25 km/h
 backwards: 0-7 km/h and 0-16 km/h

TURNING CIRCLE

120 cm

BRAKES

Wet discs

PTO

2200 rpm., with stop mechanism when mower is lifted

FUEL TANK CAPACITY

50.5 litres

LxWxH

2415 x 1370 x 1930 mm

GROUND CLEARANCE

140 mm

TREAD

front: 940 mm rear: 995 mm

WEIGHT with ROB

CM314: 755 kg **CM374:** 770 kg

- Fast speed
- Powersteering
- Safety switch in seat, PTO and brakes
- Front wheel differental lock
- Speed lock control
- Comfortseat with armrests
- Instrument board in adjustable steering column
- Auto/ full time 4WD can be switch from the seat
- Weight transfer from mower to tractor

<i>Code:</i>	<i>Description:</i>		<i>Euro:</i>
CM314	CM314 without mower with turf tires	F: 24x13.00-12 R: 20x8-10	19,500,-
CM374	CM374 without mower with turf tires	F: 24x13.00-12 R: 20x8-10	23,500,-
CM374S	CM374S without mower with turf tires	F: 24x13,00-12 R: 20x8-10	24,500,-
TBCM314	Terra tires (additional net price)	F: 24x13.00-12 R: 20x8-10	420,-



ACCESSOIRES SHIBAURA CM314/ CM374

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
SCM60S	SHIBAURA FRONTMOWER 1.50 m side discharge, 7 stage cutting height adjustments from 38 to 115 mm, mower can be lifted up 90° for easy cleaning and maintenance, 170 kg	3,600,-
PA-137SH	Mulchset 1,50 (net)	650,-
8420040	WIEDENMANN MOWER 1.50 m rear discharge	5,400,-
1200451	Mulchset	650,-
8440040	WIEDENMANN MOWER 1.80 m rear discharge	6,800,-
1200452	Mulchset	850,-
8430040	WIEDENMANN MOWER 1.80 m side discharge	6,900,-
MUFM140-31	MÜTHING Flailmower 1.40 m	5,300,-
MUFM160-31	MÜTHING Flailmower 1.60 m	5,600,-
MATT250	MATTSSON / CARONI Triplex Rotary mower 2,50 m	14,500,-
LA325EF	LASTEC three deck rotary mower 1.80 m, rear discharge	12,550,-
LA521FH	LASTEC five deck rotary mower 2.50 m, rear discharge	21,000,-
LAMULCH	Mulchsatz	605,-
CMBUMP	REAR WEIGHT bumpershape: ± 100 kg	605,-
KDE	Lift triangle	725,-
KS235	WALTER MAUSER COMFORT CABIN standard with safetyglass, lighting, removable doors, heating mounted in the roof	6,900,-
ZLAMP	Montage (net) Flashing light	400,- 50,-
PM703	GRASSCOLLECTOR hydraulic high dump ca. 2.05 m with very powerfull turbine	7,950,-
	Mounting (net)	700,-



ACCESSOIRES SHIBAURA CM314/ CM374

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
	WIEDENMANN SWEEPER incl. hydr. side adjustment type 2350	
23532503	Complete with brush 1.30 x ø 0.42 m	3,900,-
23542505	Complete with brush 1.50 x ø 0.42 m	4,200,-
023519	Dust collector 1.30 m	640,-
023529	Dust collector 1.50 m	760,-
023506	Side brush ø 0.52 m, driven by V-belt	640,-
	SNOW BLADE incl. hydr. side adjustment type 3406	
34060040	Folding blade incl. plastic scraping rib 1.60 m	2,050,-
1317235	Lift triangle	620,-
BASICL1400	CERRUTTI SNOWBLOWER 1.40 m incl. hydr. side adjustment	6,700,-
P170	HYDROMANN SALTSREADER 170 l., above motorhood	8,550,-
100EL	HYDROMANN SPREADER 12 volt, 100 litres	3,140,-
46020040	WIEDENMANN LEAFBLOWER Whispter Twister	6.900,-
336019133	Tire 20x8-10 per piece	305,-
336035711	Tire 24x13,00-12 per piece	620,-



SHIBAURA FAIRWAY MOWER SR370

AUTOMATIC FOURWHEELDRIVE

When the front wheels are slipping 4%, the fourwheeldrive is automatically engaged.

ENGINE

3 cylinder, low noise, watercooled Shibauro diesel engine
19.0 kW / 26.2 HP (SAE) 16.8 kW / 22.8 HP (DIN) 1331 cc

TRANSMISSION

Hydrost./ 2 WD: forwards: 0-16 km/h, backwards: 0-6 km/h
4 WD: forwards: 0-8 km/h, backwards: 0-3 km/h

DRIVE

Comfortable hydraulic operation with 2 groups.

CUTTING UNIT

3; diameter 178 mm x width 660 mm; 7-blade (standard)

CUTTING HEIGHT

10 - 60 mm

ROLLER

Front : diameter 80 mm, groove roller

Rear : diameter 76,3 mm, smooth roller

FUEL TANK CAPACITY

28 litre

LxWxH

2550x2030x1400 mm

WEIGHT

970 kg

- Powersteering
- Steering column in height and hook adjustable
- Self-cleaning radiator
- Instrument board in steering column
- "Backklappen"

Code:
SR370

Description:
SR370
with turf-tires F: 20x10,00-12 R: 20x10,00-10

Euro:
38,800,-



SHIBAURA FAIRWAY MOWER SR525

AUTOMATIC FOURWHEELDRIVE

When the front wheels are slipping 4%, the fourwheeldrive is automatically engaged.

ENGINE

3 cylinder, low noise, watercooled Shibauro diesel engine 31,0 kW / 43,7 HP (SAE) 27,9 kW / 38.0 HP (DIN) 1662 cc

TRANSMISSION

Hydrost./ 2 groups: forwards: 0-10 km/h and 0-17 km/h
backwards: 0-7 km/h and 0-12 km/h

DRIVE

Automatic four wheel drive or full time four wheel drive
Comfortable hydraulic operation and mechanical driven for safe working on hills.

CUTTING UNIT

5; diameter 178 mm x width 560 mm; 9-blade (standard)

CUTTING HEIGHT

7 - 32 mm

ROLLER

Front : diameter 80 mm, groove roller

Rear : diameter 76,3 mm, smooth roller

FUEL TANK CAPACITY

41 litre

LxWxH

2700x2900x2040 mm (transportwidth 2240 mm)

WEIGHT

1300 kg

- Powersteering
- Safety switch in seat, PTO and brakes
- Comfortseat with armrests
- Speed lock control
- Instrument board in adjustable steering column
- Mowing and transport speed
- "Backlappen"

Code:
SR525

Description:
SR525

with turf-tires F: 24x13,00-12 R: 20x8-10

Euro:
49,900,-



ACCESSORIES SHIBAURA SR525

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
CABSR	HARA Cabin safety glass, flashing light, wiper, interior light	6,720,-
HCABAIR	Air conditioning	4,300,-
590689	Roof	760,-
551160	Protective net (not for Cabin)	510,-
A82010090/100	Grascollector (5 pieces)	1,565,-
A72310070	Front roller scraper per piece	50,-
A72310060	Rear roller scraper per piece	25,-
FGBORSTEL	Driven rear brushes (5 pieces)	3,050,-



SHIBAURA HANDGREENSMOWER GM222

ENGINE	Robin, EH17-2B air-cooled 5.0 kW/ 6.9 hp (SAE) 4.4 kW/ 6.0 hp (DIN) 2000 rpm, 172 cc Cutting width: 560 mm Cutting height: maximum 22.2 mm
TRANSMISSION	Travelling speed (forward): 8.4 km/h with transport wheels Roller rear: aluminium, diameter 190 mm Roller front: machined steel, diameter 60 mm
REEL MOWER	Diameter: 127 mm Number of knives: 11 Capacity grasscollector: 3.2 kg
FUEL TANK CAPACITY	2.5 liter
LxWxH	940x956x1190 mm
WEIGHT	99.5 kg
- Standard groomer	

Code:
GM222

Description:
GM222

Euro:
7,250,-



SHIBAURA ROUGH TERRAIN-/ SLOPEMOWER SG280

FOURWHEELDRIVE

ENGINE

3 cylinder, low noise, watercooled Shibauro diesel engine
23.4 kW / 32.2 hp (SAE) 20.6 kW / 28.0 hp (DIN) 1496 cc

TRANSMISSION

Hydrostatic/ 2 WD: forward: 0-18 km/h, backward: 0-9 km/h
4 WD: forward: 0-12 km/h, backward: 0-6 km/h

TRANSMISSION

Comfortable hydrostatic drive with 2 groups.

FUEL TANK CAPACITY

26 litre

LxWxH

2495x1590x1730 mm

WEIGHT

770 kg

- Powersteering

- Instrument board

- Seat is horizontal adjustable for comfortable driving on hills

Code:

SG280

Description:

SG280

tires F: 21x11,00-10

R: 21x11,00-10

Euro:

29,500,-

MM60DSG

SHIBAURA midmounted mower 1.50 m side discharge

3,500,-

MM62DSGRD

FGM midmounted mower 1.50 m rear discharge

4,200,-

FEU140

FEUCHT longgrass midm. mower 1.40m rear discharge

3,980,-

FEUSPER

Hydraulic sperdifferential
Mounting (net)

590,-

280,-



SHIBAURA SUBCOMPACTTRACTOR SX24

ENGINE	3 cylinder, low noise, watercooled Shibaura diesel engine 20.5 kW / 27,6 hp (SAE) 17.9 kW / 24.0 hp DIN 1005 cc
TRANSMISSION	Hydrost. / 2 groups: forwards: 0-8 km/h and 0-17 km/h backwards: 0-6 km/h and 0-11 km/h
REAR PTO	Independent: rear 540 rpm., mid 2185 rpm.
3-POINT LINKAGE	Cat. 1 with lifting capacity 705 kg
TOWABLE MASS	1300 kg
HYDR. CAPACITY	21 litres/ min. at 130 bar Standard spool valve with 2 connections rear
TURNING RADIUS	218 cm
TREAD	front: 940 mm rear: 870 mm
GROUND CLEARANCE	230 mm
FUEL TANK CAPACITY	29.5 litres
FLOOR	Flat floor without handles
LxWxH	2493 x 1175 x 2288 mm
WEIGHT with ROB	696 kg

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
SX24	SX24 (incl. tires as desired)	13,600,-

Choice tires:

- AGSX24	Agri-tires	F: 4.00-9	R: 7-14
- WTTX24	Wide turf-tires	F: 18x8.5-8	R: 26x12.00-12
- TERRASX24	Terra-tires	F: 18x8.5-8	R: 26x12.00-12

ACCESSORIES ON PAGE:

15, 16, 30, 31, 32, 33



ACCESSORIES SHIBAURA SX24

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
	SHIBAURA MIDMOUNTED MOWER	
SXM54	Midmounted mower, working width 1.37 m	2,600,-
SXM60	Midmounted, working width 1.50 m	3,100,-
1317045	Indep. liftkit for midmounted mower (PA-122SH necessary)	520,-
PA-148SH	Mulchset 1.37 m (net)	650,-
PA-137SH	Mulchset 1.50 m (net)	650,-
	LEWIS MIDMOUNTED MOWER	
LMA120RDSX	Working width 1.20 m reardischarge	3,100,-
LMA150RDSX	Working width 1.50 m reardischarge	3,300,-
LMA120MKIT	Mulchset 1.20 m (net)	650,-
LMA150MKIT	Mulchset 1.50 m (net)	650,-
	PAULI FRONTLIFT	
PA-115SH	Frontlift with quick coupling	1.350,-
PA-120SH	Front PTO, 2000 rpm. (only with PA-125SH)	980,-
PA-122SH	Hydraulic set, 2 valves, 4 hydr. connections 2F en 2R Mounting (net)	980,- 170,-
340003281/60441	Double acting valve with two quick coupling rear Mounting (net)	710,- 115,-
	MATEV GRASSCOLLECTOR	
1317127	Grasscollector CS-G650, 650 litres	4,550,-
131729	Grasscollector CS-H650 litres with hydraulic hightipping	5,990,-
1317003	Duo airtyres 260x85	600,-
1317026	Mower connection with pipe	830,-
	MORGNIEUX GRASSCOLLECTOR	
Turbo530LD	Grasscollector 530LD, 530 litres with manual opening	3,300,-
Turbo530HD	Grasscollector 530HD, 530 litres with hydraulic hightipping	4,990,-
V04A80	Pair of wheels	660,-
V04A82	Road lights	190,-
V04A85	Full container buzzer	205,-



ACCESSORIES SHIBAURA SX24

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
KS324	WALTER MAUSER COMFORT CABIN safetyglass, electr. windscreen wiper with sprayer, heating, removable and lockable doors, outside mirror, sunblind (O.E.C.D. tested) Mounting (net)	5,450,- 340,-
ZLAMP	Flashing light	50,-
HARASX	HARA DELUXE KABINE inkl. Heizung	5,450,-
3403 00 40	SNOWBLADE incl. hydr. side adjustment incl. plastic scraping rib 1.40 m	1,680,-
TU06.03.00SX	TUCHEL SWEEPER type Simplex 400 Sweeper 1,35x Ø 0,40 m incl. hydr. side adjustment	3,140,-
TU06.03.SXSB	Dustcollector	620,-
TU06.03.SXSK	Side brush hydraulic	1,160,-
TU06.03.SXST	Dustprotector	190,-
BASICL1200	CERRUTI SNOWBLOWER Working with 1.20 m	5,600,-
LL15	LEWIS FRONTLOADER Frontloader with double acting liftcylinders and hydraulic operation of the instruments Mounting (net)	3,990,- 305,-
LBKT1.1ME	Bucket 1,1 m	630,-
LMKFK7E	Manure fork	600,-
PA-129SH	Towing-hook rear	540,-
999999004	Frontweight 27 kg (max. 3 pieces) per piece	75,-
STEUNSX	Bracket for mounting frontweight	60,-
Z622.735	Drawbar cat. 1	75,-
HEFBOK	Lift triangle with towing ball	130,-



SHIBAURA ST318M/ ST318HST

FOURWHEELDRIVE ENGINE

3 cylinder, low noise, watercooled Shibaura diesel engine
15.8 kW / 21,6 hp (SAE) 13.8 kW / 18.8 hp (DIN) 954 cc

TRANSMISSION

ST318M 9 F: 1-18 km/h; 3 R: 2-13 km/h
ST318HST 2 groups: forwards: 0-6 km/h and 0-19 km/h
backwards: 0-4 km/h and 0-11 km/h

PTO MID PTO

540 rpm.
Standard 2000 rpm.

3-POINT LINKAGE

Cat. 1 with lifting capacity 700 kg

TOWABLE MASS

2000 kg

POWERSTEERING

Standard

HYDR. CAPACITY

17 litres/ min., at 130 bar
standard spool valve with 3 connections rear

TURNING RADIUS

218 cm

TREAD

front: 822 mm rear: 851 mm

GROUND CLEARANCE

270 mm

FUEL TANK CAPACITY

20 litres

FLOOR

Almost flat floor without handles

LxWxH

2728 x 1042 x 2287 mm

WEIGHT with ROB

ST318M: 742 kg **ST318HST:** 754 kg

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
ST318M	ST318M Mechanical driven (incl. tires as desired)	13,500,-
ST318H	ST318H Hydrostatical driven (incl. tires as desired)	15,300,-

Choice tires:

- AGST321	Agri-tires	F: 6x12	R: 9.5-16
- WTTST321	Wide turf-tires	F: 20x8.00-10	R: 29x12.00-15

Additional net price tires:

- SGST321	Turf-/ transport tires	F: 6x12	R: 9.5x16	630,-
- TBST321	Terra tires	F: 20x8.5-10	R: 29x12.5-15	630,-
- INDST321	Industry tires	F: 23x8.50-12	R: 12x16.5	1,200,-

ACCESSORIES ON PAGE:

20, 21, 30, 31, 32, 33



SHIBAURA ST321M/ ST321HST

FOURWHEELDRIVE ENGINE

3 cylinder, low noise, watercooled Shibauro diesel engine
18.1 kW / 24.2 hp (SAE) 15.7 kW / 21.0 hp (DIN) 1005 cc

TRANSMISSION

ST321M 9 F: 1-18 km/h; 3 R: 2-13 km/h
ST321HST 2 groups: forwards: 0-6 km/h and 0-19 km/h
backwards: 0-4 km/h and 0-11 km/h

PTO

540 rpm.

MID PTO

Standard 2000 rpm.

3-POINT LINKAGE

Cat. 1 with lifting capacity 700 kg

TOWABLE MASS

2000 kg

POWERSTEERING

Standard

HYDR. CAPACITY

17 litres/ min., at 130 bar
standard spool valve with 3 connections rear

TURNING RADIUS

218 cm

TREAD

front: 822 mm rear: 851 mm

GROUND CLEARANCE

270 mm

FUEL TANK CAPACITY

20 litres

FLOOR

Almost flat floor without handles

LxWxH

2728 x 1138 x 2287 mm

WEIGHT with ROB

ST321M: 744 kg **ST321HST**: 756 kg

Code:

ST321M

Description:

ST321M Mechanical driven (incl. tires as desired)

ST321H

ST321H Hydrostatical driven (incl. tires as desired)

Euro:

15,600,-

17,400,-

Choice tires:

- AGST321	Agri-tires	F: 6x12	R: 9.5-16
- WTTST321	Wide turf-tires	F: 20x8.00-10	R: 29x12.00-15

Additional net price tires:

- SGST321	Turf-/ transport tires	F: 6x12	R: 9.5x16	630,-
- TBST321	Terra tires	F: 20x8.5-10	R: 29x12.5-15	630,-
- INDST321	Industry tires	F: 23x8.50-12	R: 12x16.5	1,200,-

ACCESSORIES ON PAGE:

20, 21, 30, 31, 32, 33



SHIBAURA ST324M/ ST324HST

FOUR WHEELDRIVE ENGINE

3 cylinder, low noise, watercooled Shibaura diesel engine
20.5 kW / 27.9 hp (SAE) 17.9 kW / 24.3 hp (DIN) 1131 cc

TRANSMISSION

ST324M 9 F: 1-18 km/h; 3 R: 2-13 km/h
ST324HST 2 groups: forwards: 0-6 km/h and 0-19 km/h
backwards: 0-4 km/h and 0-11 km/h

PTO

540 rpm.

MID PTO

Standard 2000 rpm.

3-POINT LINKAGE

Cat. 1 with lifting capacity 700 kg

TOWABLE MASS

2000 kg

POWERSTEERING

Standard

HYDR. CAPACITY

17 litres/ min., at 130 bar
standard spool valve with 3 connections rear

TURNING RADIUS

218 cm

TREAD

front: 822 mm rear: 851 mm

GROUND CLEARANCE

270 mm

FUEL TANK CAPACITY

20 litres

FLOOR

Almost flat floor without handles

LxWxH

2728 x 1042 x 2287 mm

WEIGHT with ROB

ST324M: 750 kg **ST324HST:** 762 kg

Code:

Description:

Euro:

ST324M

ST324M Mechanical driven (incl. tires as desired)

17,700,-

ST324H

ST324H Hydrostatical driven (incl. tires as desired)

19,500,-

Choice tires:

- AGST321	Agri-tires	F: 6x12	R: 9.5-16
- WTTST321	Wide turf-tires	F: 20x8.00-10	R: 29x12.00-15

Additional net price tires:

- SGST321	Turf-/ transport tires	F: 6x12	R: 9.5x16	630,-
- TBST321	Terra tires	F: 20x8.5-10	R: 29x12.5-15	630,-
- INDST321	Industry tires	F: 23x8.50-12	R: 12x16.5	1,200,-

ACCESSORIES ON PAGE:

20, 21, 30, 31, 32, 33



ACCESSORIES ST318/ ST321/ ST324

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
	SHIBAURA MIDMOUNTED MOWER	
STM60-ST318	mower 1.50 m, side discharge	3,100,-
PA-137SH	Mulchset 1.50 m (net)	650,-
	PAULI FRONTLIFT	
PA-145SH	Frontlift with quick coupling	1,250,-
PA-140SH	Front PTO (only with PA-145SH)	980,-
PA-146SH	Hydraulic set, 2 hydr. connections front with joystick	980,-
	Mounting (net)	170,-
	MATEV GRASSCOLLECTOR	
317127	Grasscollector CS-G650, 650 litres	4,550,-
317129	Grascollector CS-H650, 650 litres with hydraulic hightipping	5,990,-
1317003	Duo airtyres 260x85	610,-
1317026	Mower connection with pipe	830,-
	MORGNIEUX GRASSCOLLECTOR	
Turbo530LD	Grasscollector 530LD, 530 litres with manual opening	3,300,-
Turbo530HD	Grasscollector 530HD, 530 litres with hydraulic hightipping	4,990,-
V04A80	Pair of wheels	660,-
V04A82	Road lights	190,-
V04A85	Full container buzzer	205,-
KS321	WALTER MAUSER COMFORT CABIN	5,990,-
	safety glass, electr. windscreen wiper with sprayer, heating, sunblind, removable and lockable doors, outside mirror (O.E.C.D. tested)	
	Mounting (net)	340,-
ZLAMP	Flashing light	50,-



ACCESSORIES ST318/ ST321/ ST324

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
	LEWIS FRONTLOADER	
LL18	Frontloader with double acting liftcylinders and hydraulic operation of the instruments	4,990,-
	Mounting (net)	305,-
LMKFK7D	Manure fork	730,-
LBKT1.2D	Bucket 1.2 m	830,-
	SNOWBLADE incl. hydr. side adjustment	
3403 00 40	incl. plastic scraping rib 1.40 m	1,680,-
3406 00 40	incl. plastic scraping rib 1.50 m	1,940,-
	TUCHEL SWEEPER type Simplex 400	
TU06.03.00SX	Sweeper 1,35x Ø 0,40 m incl. hydr. side adjustment	3,140,-
TU06.03.SXSB	Dustcollector	620,-
TU06.03.SXSK	Side brush hydraulic	1,160,-
TU06.03.SXST	Dustprotector	190,-
	OTHER	
SPTREKHA	Towing-hook rear	420,-
999999004	Frontweight 27 kg (max. 3 pieces) per piece	75,-
Z622.735	Drawbar cat. 1	75,-
HEFBOK	Lift triangle with towing ball	130,-
PA-ST318	Mudguardset front	540,-
KU318L	Support for adjustable towing ball- and trailer hitchcoupling	525,-
INK50/199-329060	Adjustable towing ball coupling	350,-
KU5141/199-ZB	Adjustable trailer hitchcoupling	350,-



SHIBAURA ST330M/ ST330HST

FOUR WHEELDRIVE ENGINE

3 cylinder, low noise, watercooled Shibaura diesel engine
25.8 kW / 34.5 hp (SAE) 22.4 kW / 30.0 hp (DIN) 1496 cc

TRANSMISSION

ST330M 9 F: 1-24 km/h 3 R: 2-16 km/h

ST330HST 3 groups:

forwards: 0-6 km/h, 0-13 km/h and 0-29 km/h

backwards: 0-4 km/h, 0-9 km/h and 0-18 km/h

PTO

540 rpm.

MID PTO

Standard on hydrostat

3-POINT LINKAGE

Cat. 1 with lifting capacity 1400 kg

TOWABLE MASS

2800 kg

HYDR. CAPACITY

27 litres/ min., at 130 bar

standard spool valve with 2 connections rear

TURNING RADIUS

276 cm

POWERSTEERING

Standard

TREAD

front: 1100 mm rear: 1115 mm

GROUND CLEARANCE

300 mm

FUEL TANK CAPACITY

30 litres

FLOOR

Almost flat floor without grips

LxWxH

2830 x 1400 x 2490 mm (agri-tyres)

WEIGHT with ROB

ST330M: 1085 kg **ST330HST:** 1075 kg

Code:

ST330M

ST330H

Description:

ST330M Mechanical driven (incl. tires as desired)

ST330H Hydrostatical driven (incl. tires as desired)

Euro:

19,800,-

21,600,-

Choice tires:

- AGST333 Agri-tires

F: 6x14

R: 9.5x24

- WTTST333 Wide turf-tires

F: 25x8.50-14

R: 13.6x16

Additional net price tires:

- SGST333 Turf-/ transport tires

F: 7x14

R: 11.2x24

800,-

- INDST333 Industry tires

F: 27x8.5-15

R: 400/55-22.5

1,200,-

ACCESSORIES ON PAGE:

24, 25, 30, 31, 32, 33



SHIBAURA ST333M/ ST333HST

FOUR WHEELDRIVE ENGINE

3 cylinder, low noise, watercooled Shibaura diesel engine
28.3 kW / 37.9 hp (SAE) 24.6 kW / 33.0 hp (DIN) 1496 cc

TRANSMISSION

ST333M 9 F: 1-24 km/h 3 R: 2-16 km/h

ST333HST 3 groups:

forwards: 0-6 km/h, 0-13 km/h and 0-29 km/h

backwards: 0-4 km/h, 0-9 km/h and 0-18 km/h

PTO

540 rpm.

MID PTO

Standard on hydrostat

3-POINT LINKAGE

Cat. 1 with lifting capacity 1400 kg

TOWABLE MASS

2800 kg

HYDR. CAPACITY

27 litres/ min., at 130 bar

standard spool valve with 2 connections rear

TURNING RADIUS

276 cm

POWERSTEERING

Standard

TREAD

front: 1100 mm rear: 1115 mm

GROUND CLEARANCE

300 mm

FUEL TANK CAPACITY

30 litres

FLOOR

Almost flat floor without grips

LxWxH

2830 x 1400 x 2490 mm (agri-tyres)

WEIGHT with ROB

ST333M: 1100 kg **ST333HST:** 1090 kg

Code:

Description:

Euro:

ST333M

ST333M Mechanical driven (incl. tires as desired)

21,600,-

ST333H

ST333H Hydrostatical driven (incl. tires as desired)

23,400,-

Choice tires:

- AGST333	Agri-tires	F: 7x14	R: 11.2x24
- WTTST333	Wide turf-tires	F: 25x8.50-14	R: 13.6x16

Additional net price tires:

- SGST333	Turf-/ transport tires	F: 7x14	R: 11.2x24	800,-
- INDST333	Industry tires	F: 27x8.5-15	R: 400/55-22.5	1,200,-

ACCESSORIES ON PAGE:

24, 25, 30, 31, 32, 33



ACCESSORIES SHIBAURA ST330/ ST333

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
STM60-ST330 PA-137SH	SHIBAURA midmounted mower 1.50 m hydr. lifting Mulchset 1.50 m (net)	3,990,- 650,-
MATEV GRASSCOLLECTOR		
317085	Grasscollector CS-850, 850 litres	5,190,-
317086	Grasscollector CS-H850, 850 litres wiht hydraulic tipping	6,650,-
1315753	Dismounting frame	380,-
1315748	Airtyres 11 x 7/4 (recommended option)	1,090,-
1315715	Mower connection with pipe	1,090,-
MORGNIEUX GRASSCOLLECTOR		
Turbo790LD	Grasscollector 790LD, 790 litres with manual opening	4,390,-
Turbo790HD	Grasscollector 790HD, 790 litres with hydraulic hightipping	5,990,-
V04A80	Pair of wheels	660,-
V04A82	Road lights	190,-
V04A85	Full container buzzer	205,-
KS329	WALTER MAUSER COMFORT CABIN safetyglass, electr. windscreen wiper with sprayer, heating, removable and lockable doors, outside mirror, sunblind (O.E.C.D. tested)	6,200,-
ZLAMP	Mounting (net) Flashing light	390,- 50,-
PAULI FRONTLIFT		
PA-135SH	Frontlift with quick coupling	1,250,-
PA-130SH	Front PTO for HST (only with PA-135SH)	980,-
PA-136SH	Hydraulic set, 2 hydr. connections front with joystick Mounting (net)	980,- 170,-
PAULI FRONTLIFT PROFI		
PA-170/175SH	Frontlift + Front PTO, electr. magnetcoupling, 1000 rpm.	4,750,-
PA-160SH	Hydr. set, 2 hydr. connections front with joystick Mounting (net)	980,- 420,-



ACCESSORIES SHIBAURA ST330/ ST333

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
23542506	WIEDENMANN SWEEPER type 2350	
023529	Sweeper 1.50 m incl. side bearing	4,240,-
023506	Dust collector 1.50 m	700,-
	Side brush ø 0.52 m driven by V-belt	610,-
	SNOWBLADE incl. hydr. side adjustment	
3406 00 40	incl. plastic scraping rib 1.60 m	1,940,-
PA-4130K	incl. plastic scraping rib 1.80 m	2.150,-
	LEWIS FRONTLOADER	
LL25	Frontloader double acting liftcylinders and hydr. operation	5,840,-
	Mounting (net)	305,-
LBKT1.1MQA	Bucket 1.1 m	780,-
LBKT1.3MQA	Bucket 1.3 m	930,-
LMKFK7QA	Manure fork	840,-
LPFKA01QA	Pallet fork	1,375,-
LDOZA1.6A	Frontblade 1.6 m	1,950,-
DB1.6RWS	Rubber wearstrip for blade 1.6 m	210,-
DB02HAC	Extra price hydr. side adjustment with 2 cylinders	450,-
PDFR	Extra price third funktion (notwendig for snowblade)	450,-
	OTHERS	
SPTREKHA	Towing-hook rear	420,-
999999004	Frontweight 27 kg (max. 4 pieces) p./ piece	75,-
Z622.735	Drawbar cat. 1	75,-
HEFBOK	Lift triangle with towing ball	130,-
PA-162SH	Mudguardset front	540,-
KU318L	Support for adjustable towing ball- and trailer hitchcoupling	525,-
INK50/199-329060	Adjustable towing ball coupling	350,-
KU5141/199-ZB	Adjustable trailer hitchcoupling	350,-
WEMPEDAL	HST Autopedal	350,-



SHIBAURA ST445SSS

FOUR WHEELDRIVE ENGINE

4 cylinder, low noise, watercooled Shibaura diesel engine
38.6 kW / 51.8 hp (SAE) 33.6 kW / 45.0 hp (DIN) 2216 cc

TRANSMISSION

Shuttle-shift synchronised 24 forwards and 24 backwards

Forwards: 0-6 km/h, 0-13 km/h and 0-29 km/h

Backwards: 0-4 km/h, 0-9 km/h and 0-18 km/h

PTO

Independent 540 and 790 rpm.

CREEPER SPEED

From 150 m/h

3-POINT LINKAGE

Cat. 1 with lifting capacity 1486 kg

TOWABLE MASS

2500 kg

HYDR. CAPACITY

37 litres/ min., at 175 bar

standard spool valve with 2 connections rear

TURNING RADIUS

305 cm

POWER STEERING

Standard

TREAD

front: 1155 mm rear: 1250 mm

GROUND CLEARANCE

330 mm

FUEL TANK CAPACITY

39 litres

FLOOR

Almost flat floor without handles

LxWxH

3210 x 1640 x 2470 mm

WEIGHT with ROB

1510 kg

Code:

ST445

Description:

ST445 (incl. tires as desired)

Euro:

24,900,-

Choice tyres:

- AGST445 Agri-tires F: 8.00x16 R: 14.9x24
- WTTST445 Wide turf-tires F: 27x8.50-15 R: 475/80D20

ACCESSORIES ON PAGE:

27, 30, 31, 32, 33



ACCESSORIES SHIBAURA ST445SSS

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
AS435	COMFORT CABIN safety glass, electr. windscreen wiper with sprayer, heating, removable and lockable doors, outside mirror, sunblind (O.E.C.D. tested)	7,600,-
ZLAMP	Mounting (net) Flashing light	440,- 50,-
	PAULI FRONTLIFT PROFI	
PA-195SH	Frontlift with quick coupling	2,590,-
PA-190SH	Front PTO, electr. magnetcoupling, 1000 rpm.	2,870,-
PA-196SH	Hydr. set, 2 hydr. connections front with joystick	990,-
	Mounting (net)	440,-
	OTHERS	
SPTREKHA	Towing-hook rear	420,-
999999004	Frontweight 27 kg (max. 4 pieces) p. piece	80,-
999999003	Drawbar cat. 1	80,-
HEFBOK	Lift triangle with towing ball	130,-
	LEWIS FRONTLOADER	
LL38	Frontloader with double acting liftcylinder and hydraulic operation of the instruments	6,890,-
	Mounting (net)	305,-
LBKT1.1MA	Bucket 1.1 m	780,-
LBKT1.3MA	Bucket 1.3 m	950,-
LBKT1.5MA	Bucket 1.5 m	1,250,-
LMKFK9QA	Manure fork 1.25 m	1,100,-
LLDOZA1.8A	Frontblade 1.8 m	2,200,-
DB02HAC	Extra price hydr. side adjustment with 2 cylinders	450,-



SHIBAURA ST450HST

FOUR WHEELDRIVE ENGINE

4 cylinder, low noise, watercooled Shibaura diesel engine
42 kW / 55.5 hp (SAE) 36 kW / 48.3 hp (DIN) 2216 cc

TRANSMISSION

Hydrostatic feature separate forward and reverse pedals
and power shift control that doubles your speed choices
by providing a "High" and "Low" at any speed in either
range and provides Easy Operation.

Forwards: 0 - 30 km/h; Backwards: 0 - 21 km/h

Independent 540 and 750 rpm.

Standard 2000 rpm.

PTO

MID PTO

3-POINT LINKAGE

TURNING RADIUS

Cat. 1 with lifting capacity 1486 kg

270 cm

TREAD

F: 1150 mm R: 1130 mm

POWER STEERING

Standard

FUEL TANK CAPACITY

54 litres

FLOOR

Almost flat floor without handles

LxWxH

3210 x 1470 x 2470 mm

WEIGHT with ROB

1550 kg

Code:

ST450

Description:

ST450HST (incl. tires as desired)

Euro:

28,500,-

Choice tires:

- AGST450	Agri-tires	F: 8.00x16	R: 14.9x24
- WTTST450	Wide turf-tires	F: 27x8.50-15	R: 475/80D20
- R4ST450	Industry tires	F: 10-16.5	R: 17.5L-24
- FDST450	Narrow turf tires	F: 8-16	F: 13.6/ 12-28

PAULI FRONTLIFT

PA-450SH	Frontlift with quick coupling	1,800,-
PA-451SH	Front PTO	1,280,-
PA-452SH	Hydraulic set, 2 hydr. connections front with joystick Mounting (net)	980,- 270,-



SHIBAURA EUROPE BV

SHIBAURA ST460EHSS

FOUR WHEELDRIVE ENGINE

4 cylinder, low noise, watercooled Shibaura diesel engine
51.5 kW / 69 hp (SAE) 44.7 kW / 60 hp (DIN) 2216 cc

TRANSMISSION

Electro-Hydraulic-Shuttle-Shift, 24 forwards 24 backwards
Forwards: 0.2 - 33 km/h Backwards: 0.2 - 34 km/h

PTO

Independent 540 and 750 rpm.

CREEPER SPEED

From 150 m/h

3-POINT LINKAGE

Cat. 1 & 2 with lifting capacity 1975 kg

TURNING RADIUS

315 cm

POWER STEERING

Standard

FUEL TANK CAPACITY

54 litres

FLOOR

Almost flat floor without handles

LxWxH

3601 x 1718 to 2322 x 2585 mm

WEIGHT with ROB

AG: 1920 kg TURF: 1835 kg

Code:

ST460

Description:

ST460EHSS (incl. tires as desired)

Euro:

31,400,-

Choice tires:

- AGST460	Agri-tires	F: 8.00x16	R: 14.9x24
- WTTST460	Wide turf-tires	F: 27x8.50-15	R: 475/80D20

PAULI FRONTLIFT PROFI

PA-460SH	Frontlift with quick coupling	2,800,-
PA-461SH	Front PTO, electr. magnetcoupling, 1000 rpm.	3,100,-
PA-462SH	Hydr. set, 2 hydr. connections front with joystick	980,-
	Mounting (net)	460,-



SET TIRES (all prices (net) are per 4 (2 front- and 2 reartires))

<i>Code:</i>	SX24			<i>Euro:</i>
AGSX24	Agri-tires	F: 4.00-9	R: 7-14	830,-
WTT SX24	Wide Turf-tires	F: 18x8.5-8	R: 26x12.00x12	1,180,-
TERRASX24	Terra-tires	F: 18x8.5-8	R: 26x12.00x12	1,180,-

<i>Code:</i>	ST318/ ST321/ ST324			<i>Euro:</i>
AGST321	Agri-tires	F: 6x12	R: 9.5x16	1,630,-
SGST321	Turf-/ transport tires	F: 6x12	R: 9.5x16	1,890,-
WTTST321	Wide Turf-tires	F: 20x8.00-10	R: 29x12.00-15	1,790,-

<i>Code:</i>	ST330/ ST333			<i>Euro:</i>
AGST330	Agri-tires ST330	F: 6x14	R: 9,5x24	1,940,-
AGST333	Agri-tires ST333	F: 7x14	R: 11,2x24	2,060,-
SGST333	Turf-/ transport tires	F: 7x14	R: 11.2x24	2,470,-
WTTST333	Wide turf-tires	F: 25x8.50-14	R: 13.6x16	2,400,-

<i>Code:</i>	ST445			<i>Euro:</i>
AGST445	Agri-tires	F: 8x16	R: 14.9x24	2,580,-
WTTST445	Turf-tires	F: 27x8.50x15	R: 475/80D20	3,930,-

COMPLETE ENGINES (exclusive cooler)

<i>Code:</i>	<i>Tractor type:</i>	<i>Dieselenigne:</i>	<i>Euro:</i>
138707	GT161	E673-GT75	3,840,-
138606	CM214	S773-CM214	4,200,-
139232	CM314	N843-D-MC30	5,160,-
139234	CM374	N843L-D-MC36	5,640,-
138642	SX24	S773-C-24-0.5	4,200,-
133535	ST318	S753-3-ST318-ISO	3,960,-
138612	ST321	S773-ST321-ISO	4,200,-
138614	ST324	S773L-ST324-ISO	4,560,-
139239	ST330	N843-D-ST330	5,160,-
139156	ST333	N843-ST333-01	5,400,-
133660	ST445	N844L-C-ST445	6,720,-
133794	ST460	N844LT-D-ST460	7,650,-



ROTARY MOWERS FOR TRACTORS

<i>Code:</i>	<i>Dis-charge</i>	<i>Working width</i>	<i>PTO rpm</i>	<i>hp</i>	<i>Weight</i>	<i>Euro:</i>
Wiedemann frontmowers						
4530040	Side	130 cm	2000t	12	180 kg	3,850,-
8380040	Rear	130 cm	2000t	12	195 kg	4,630,-
1200450	Mulchkit for 130 cm mowers with reardischarge					530,-
8400040	Side	150 cm	2000t	15	210 kg	4,360,-
8420040	Rear	150 cm	2000t	15	220 kg	4,880,-
1200451	Mulchkit for 150 cm mowers with reardischarge					640,-
8430040	Side	180 cm	2000t	20	235 kg	6,110,-
8440040	Rear	180 cm	2000t	20	245 kg	6,090,-
1200452	Mulchkit for 180 cm mowers with reardischarge					840,-
Sitrex rearmowers						
SM120L	Side	120 cm	540t	12-20	168 kg	2,040,-
SM120P	Rear	120 cm	540t	12-20	168 kg	2,150,-
SM150L	Side	150 cm	540t	15-30	197 kg	2,260,-
SM150P	Rear	150 cm	540t	15-30	197 kg	2,360,-
SM180L	Side	180 cm	540t	20-40	227 kg	2,420,-
SM180P	Rear	180 cm	540t	20-40	227 kg	2,590,-

FLAIL MOWERS FOR TRACTORS

<i>Code:</i>	<i>Working width</i>	<i>Knives</i>	<i>max. hp</i>	<i>Weight:</i>	<i>Euro:</i>
Müthing frontmowers					
MUE120-31-1	120 cm	20	50	280 kg	4,460,-
MUE140-31-1	140 cm	24	50	300 kg	4,480,-
MUE160-31-1	160 cm	28	50	330 kg	4,850,-
Müthing rearmowers					
MUE120-31	120 cm	20	25	280 kg	4,460,-
MUE140-31	140 cm	24	25	300 kg	4,680,-
MUE160-31	160cm	28	50	330 kg	4,850,-

SALT- AND FERTILIZERSREADER

Cosmo spreader with plastic funnel and stainless steel spinner, agitator for salt, oversized gearbox, cardan shaft, deflector width controller.

<i>Code:</i>	<i>Description</i>	<i>Euro:</i>
COSPLS180	COSMO Spreader, PLS180, 169 litres	1,090,-
COSPLS400	COSMO Spreader, PLS400, 300 litres	1,200,-
COSABDP	Cover	90,-
COSBEL	Lighting	90,-



SNOWBLOWERS

Model	1200S	1500S
Working width	1200 mm	1500 mm
Height without pipe	710 mm	710 mm
Height with pipe	1310 mm	1310 mm
Weight	240 kg	260 kg
Snow throw distance	8-20 m	8-20 m
Screw diameter	500 mm	500 mm
Diameter	390 mm	390 mm
Power required	20-40 hp	20-40 hp
PTO rpm	540-1000-2000 rpm.	540-1000-2000 rpm.

<i>Code:</i>	<i>Description</i>	<i>Euro:</i>
S4700029	HYDROMANN Snowblower right working width 120 cm	6,500,-
S4700011	HYDROMANN Snowblower right working width 140 cm	7,060,-



ARTIFICIAL TURF MAINTENANCE

WIEDENMANN Terra Brush

The Terra Brush straightens artificial turf fibers and levels the surface. It can be used to brush in sand and rubber granules. Helps improve ball roll and reduce danger of injuries.



<i>Code:</i>	<i>Description</i>	<i>Euro:</i>
508 0040	Terra Brush 1.85 m working width with zig-zag alignment of the individual brushes without bristle	1,020,-
1226503	Special bristles	900,-
1226506	Tractors with 3-point hitch frame	630,-
1226501	Trailer with hitch, electrical lifting 12V, 2 special wheels 18/5	2,800,-
1226502	Trailer with hitch, hydraulically lifting, 2 special wheels 18/5	1,990,-
1226441	Spring tines 1.85 m wide to loosen granulate attachable to base unit	1,320,-

WIEDENMANN Terra Clean

PTO driven artificial turf sweeper for collecting debris like leaves, paper, seeds from trees, glass splinters and pieces of plastic onto a big riddle screen. By screening the collected material, debris is separated from reusable filling material.

Pneumatic tyres : 11x7
 Dimensions : length with drawbar 230 cm,
 width 150 cm, height 120 cm
 Weight : 320 kg



<i>Code:</i>	<i>Description</i>	<i>Euro:</i>
2400040	Terra Clean 3-point mounted, working width 1.20 m	10,500,-
1240199	Lights	230,-

WIEDENMANN Terra Rake

The Terra Rake can be used for the quick and efficient removal of thatch. Its wide robust frame has five rows of spring tines arranged in a parallelogram shape.

<i>Code:</i>	<i>Description:</i>
495 00 40	Terra Rake, Width 1.60 m
120 24 35	Relieving satz



<i>Euro:</i>
3.600,-
350,-

