

# GM222

## Utmost refined Greens Mower for your ideal greens.

Superior Greens Mower for precision cutting—Tournament standard greens mower, purpose built to meet the exacting demands of the professional green keeper; Made from corrosive resistant cast aluminium for excellent structural integrity.

The GM222E follows the undulations of the ground and its 9 or 11 blade reel provides precise and high quality cutting finish.

### Groomer

The interlocking groomer reel can be easily set for both forward and reverse rotation to suit varying turf conditions. The interlocking design brings the front roller closer to the cutting cylinder, reducing roller to roller ratio and ensuring superior contour following capabilities.

### External Differential

Each half of the rear roller is driven independently through a remote differential. This enables the operator to accurately steer the mower and ensure a consistent overlap with the previous cut.



Grass Collector (standard)



Grooming Roller (standard)



Wheel For Transportation

# Superior operating and quality features.

## Comfortable Control

The precise weight balance provides comfortable control and ensures smooth turning.

## Cutting Blade Clutch Lever

Easy to reach clutch controls for safe operation.



## Cutter Cover

Cutter Cover controls wind velocity by reel rolling, scattering grass even in the grass collector.

## Engine Stop Switch

Double engine stop switches on the control panel and engine enhance safety.

## Thatching Brush (Option)

The forward and reverse rotation of the thatching brush provides superior quality of cut.



## Cylinder Options

Choice of 9 or 11 bladed cylinders for optimum cutting quality regardless of conditions.




## Gear Driver, Cutting Unit

No need to remove tyres in order to adjust thatching brush and replace the cutting blade owing to gear drive.

## Durable Rear Roller and Reel Blade

Gear drive provides excellent durability, compared to Chain drive.



## Easy belt Replacement

The belt between engine and transmission can be easily replaced without moving engine.

## Specifications

Model	GM222-A9	GM222-A11	GM222B-AC9	GM222B-AC11	GM222B-AD9	GM222B-AD11	GM222BS-AD11
<b>Dimensions</b>							
Length (mm)	1120			1160			
Width (mm)	870						
Height (mm)	910						
Weight (kg)	90.5	91.5	94.0	96.0	94.0	95.0	99.5
<b>Engine</b>							
Model	EH17-2B						EH17-2BS
Type	Air cooled 4-cycle petrol engine						
Displacement (cc)	172						
Horsepower [kW (hp)/rpm]	4.4 (6.0)/2000						
Fuel Tank Capacity (ℓ)	3.6						
Starter	Ricoil Starter						cell Starter
<b>Traveling Speed</b>							
Traveling Speed (km/h)	5.2						
<b>Cutting Width</b>							
Cutting Width (mm)	557						
<b>Cutting Height</b>							
Cutting Height (mm)	3(2.5)~30			3.5(2.5)~30			
<b>Reel Mower</b>							
Reel Diameter & Width (mm)	123×557						
Number of reel	9	11	9	11	9	11	
Bed Knife (mm)	3.5						
Attachment	—		Thatching Brush			Grooming	
<b>Standard Equipment</b>							
Standard Equipment	Bucket						
Option	—		Thin Bedknife, Groved Roller, Smooth Roller				



### Important information

● Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.

※ We reserve the right to discontinue models or change specifications without notice.

# SHIBAURA

SHIBAURA EUROPE BV

Begonialaan 7

NL - 6851 TE Huissen

T. (0031) 026 326 9999

F. (0031) 026 326 9990

E. info@shibaura.com

www.shibaura.com

Catalog No. 2673 Printed in Japan